OPERATOR'S MANUAL

Boomer[™] 40
Boomer[™] 50
with Cab
Compact Tractor



Contents

1	GENERAL INFORMATION	
	Note to the owner	
	Intended use Electro-Magnetic Compatibility (EMC)	
	Manual scope	
	Metric and Imperial units abbreviations	
	Product Identification Number (PIN)	
	Operator's manual storage	
	Machine orientation	
	Official documents	1-12
_		
2	SAFETY INFORMATION	0.4
	Safety alert symbol and signal word definition	
	Safety rules	
	Ecology and the environment	
	Safety features	
	Safety aspects	
	Tractor jacking points	
	Airborne noise emission	
	Exhaust emission levels	
	Vibration levels	
	Machine stability	
	Safety signs	
	Instructional signs	
	International symbols	2-45
3	CONTROLS AND INSTRUMENTS	
	ACCESS TO OPERATOR'S PLATFORM	
	Cab door	3-1
	Cab side window	
	Cab rear window	
	OPERATOR'S SEAT	
	Seat belt	3-4
	Seat controls	3-5
	FORWARD CONTROLS	
	Instrument cluster identification	3-6
	Cruise control	
	Transmission shuttle shift lever	3-9
	Clutch pedal	3-10
	Brake pedals	
	Foot throttle pedal	
	Hand throttle lever	
	lleme eviteb	0 4 4
	Horn switch	

Power Take-Off (PTO) switch	. 3-16
Key switch	. 3-17
Differential lock pedal	. 3-18
Hydrostatic transmission (HST) foot pedals	. 3-19
Tilt steering lever	
Multifunction light switch	
Waltiful of ingrit own.	. 0 21
LEFT-HAND SIDE CONTROLS	
Transmission range lever	. 3-22
Front-wheel drive lever	
Mid Power Take-Off (PTO) lever	
Rear PTO speed selection lever (Optional)	. 3-25
RIGHT-HAND SIDE CONTROLS	
Park brake	3-26
Hydraulic Power Lift (HPL)	. 3-27
Draft control	
Rear remote control valves	. 3-29
Mid mount two spool control valve	
Transmission main shift lever	
Hydrostatic transmission (HST) range lever	
Beacon switch	
Cab internal lighting	
Cab external lighting	
Front window wiper/washer	
Rear window wiper/washer (optional)	. 3-38
Auxiliary power outlet	. 3-39
OVERHEAD CONTROLS	
Cab climate control	3-40
Air conditioning	. 3-41
Front sun shade	
Rear-view inside mirror	
EXTERIOR CONTROLS	
Rear-view outside mirrors	3-47
Hood release latch	
OPERATING INSTRUCTIONS	
COMMISSIONING THE UNIT	
Engine break-in procedure	
Power Take-Off (PTO) operation	
Three-point hitch	
Attaching three-point equipment	4-6
Extendable drawbar	
Hydraulic lift rocker	
Hydraulic Power Lift (HPL) drop rate control valve	. 4-11

	STARTING THE UNIT	4 40
	Key switch	
	Cold starting aids	
	Starting the engine	
	Starting the tractor with jumper cables	4-19
	STOPPING THE UNIT	
	Stopping the engine	
	Emergency stopping	
	Diakes	4-22
	MOVING THE UNIT	
	Steering wheel adjustment	
	Steering operation	
	Transmission operation at low ambient temperatures	
	16 x 16 Synchronized transmission operation	
	10 x 10 Synchronized transmission operation	- -23
	PARKING THE UNIT	
	Brakes and controls - Park	4-31
5	TRANSPORT OPERATIONS	
	ROAD TRANSPORT	
	External lighting - Identification	5-1
	Hazard warning light operation	5-2
	Turn signal operation	
	Road lights operation	
	Work lights operation	
	Rear work light operation	
	Driving the vehicle	5-7
	SHIPPING TRANSPORT	
	Carrying the tractor on a transporter	5-8
	RECOVERY TRANSPORT	
	Towing	5-8
^	MODKING ODEDATIONS	
0	WORKING OPERATIONS	
	GENERAL INFORMATION	
	Tractor ballasting	
	Tractor ballasting weights	
	Liquid ballast	6-4

7 MAINTENANCE

GENERAL INFORMATION	
General information	
Battery disconnect switch	
Diesel fuel	
Biodiesel fuel	
Refueling the tractor	
Organic Acid Technology (OAT) coolant	
Change engine coolant to Organic Acid Technology (OAT) coolant	
Consumables	
Torque William tigritering torques for normal assembly	
MAINTENANCE CHART Maintenance chart	7 15
Every 10 hours or daily	
Engine oil level - Check	7-17
Engine cooling system - Check	7-18
After the first 50 hours of operation	
Engine oil and oil filter - Change	7 10
Fuel filter - Change	
Hydraulic oil filter - Replace	
Hydrostatic Transmission (HST) oil filter - Replace	
Wheel bolt / nut - Tighten	
Every 50 hours	
Grease fittings	
Transmission fluid level - Check	
Clutch pedal free play - Check	
Brake pedal free play - Check	
Hydrostatic transmission (HST) neutral adjustment - Check	
Fan belt tension - Check	7-29
Wheels and tires pressure - Check	
Front axle and differential oil level - Check	
Air cleaner - Clean	
oub all litter officer and dicarring	
F. (a.m., 400 h a.u.)	
Every 100 hours	
Fuel filter-Drain	7-35
Every 300 hours	
Engine oil and oil filter – Change	7-36
Hydraulic oil filter - Replace	
Hydrostatic Transmission (HST) oil filter - Replace	
Fuel filter - Change	
. 20	

Engine belts - Check	7-40
Wheels bolt/nut	7-41 7-41
Every 500 hours Cab air filter - Replace	7-42
Every 600 hours Front axle differential oil - Change fluid	7-43
Transmission fluid - Change	
Every 1000 hours	7.40
Air cleaner inner element - Replace	
General maintenance Fuel injection system - Bleed	7 10
Fuel injection system - Bleed	
Hydrostatic Transmission (HST) neutral adjustment	
Battery	
Alternator	
Fuse and relay box - Replace Fuse and relay box - Replace	
Maxi fuse	
Fuse and relay box Fuse - Replace	
Headlight	
Rear tail/brake/hazard/turn signal bulbsFront turn signal/hazard light bulb	
Wheels bolt/nut tighten	
Front wheels - Adjust	
Brake pedal free play - Check	7-64
Clutch pedal free play - Check	7-65
STORAGE Storage of tractor	7-66
Removal of tractor from storage	
8 TROUBLESHOOTING	
SYMPTOM(S)	
Engine - Troubleshooting	. 8-1
Clutch - Troubleshooting	
Hydraulic service brakes - Troubleshooting	
Hydraulic Lift System - Troubleshooting	
Steering - Troubleshooting	
Electrical system - Troubleshooting	

9 ;	SPECIFICATIONS	
	Wheel tread settings	
	Tire inflation pressures	9-2
	General specifications	9-3
	Tractor dimensions	9-8
10	Optional equipment	10-1
11	FORMS AND DECLARATIONS Delivery report - Owner Copy Delivery report - Dealer Copy Delivery report - Dealer Copy	11-3

1 - GENERAL INFORMATION

Note to the owner

This manual contains information concerning the adjustment and maintenance of your new equipment. You have purchased a dependable machine, but only by proper care and operation can you expect to receive the performance and long service built into this equipment. Please have all operators read this manual carefully and keep it available for ready reference.

Your NEW HOLLAND dealer will instruct you in the general operation of your new equipment. (Refer to the 'Delivery Report' at the back of this manual.) Your dealer's staff of factory-trained service technicians will be glad to answer any questions that may arise regarding the operation of your machine.

Your NEW HOLLAND dealer carries a complete line of genuine NEW HOLLAND service parts. These parts are manufactured and carefully inspected to ensure high quality and accurate fitting of any necessary replacement parts. Be prepared to give your dealer the model and product identification number of your new equipment when ordering parts. Locate these numbers now and record them below. Refer to the 'General Information' section of this manual for the location of the model and product identification numbers of your machine.

ATION

EC Declaration of Conformity

The manufacturer delivers the machine with a document called "EC Declaration of Conformity" which guarantees that the machine complies with the European Machinery Safety Directives. This document will usually be found on the machine when the machine is originally supplied to you. If not, it should be obtained from your dealer. The owner must carefully preserve this document to be able to present it to Safety Inspection Authorities when requested. The document as well as the operators manual should also stay with the machine if it is traded again.

A WARNING

Illustrations in this manual may show protective shielding open or removed to better illustrate a particular feature or adjustment.

Replace all shields before operating the machine.

Failure to comply could result in death or serious injury.

W0012A

ATTENTION: The engine and fuel system on your machine is designed and built to government emission standards. Tampering by dealer, customers, operators, and end users is strictly prohibited by law. Failure to comply

could result in government fines, rework charges, invalid warranty, legal action, and possible confiscation of the machine until rework to original condition is completed. Engine service and/or repairs must be done by a certified technician only!

Improvements

CNH America LLC is continually striving to improve its products. We reserve the right to make improvements or changes when it becomes practical and possible to do so, without incurring any obligation to make changes or additions to the equipment sold previously.

Intended use

INTENDED USE OF YOUR TRACTOR

Your tractor is designed and made to pull, to carry, and to power a variety of mounted or towed equipment, although within some physical limits. The working speed and performance may depend on a number of various parameters, such as weather and terrain conditions. Though the tractor is designed to perform in combination with a variety of equipment in most crops and conditions, there may be a number of combinations of above parameters, for which there is severe degradation of performance of the tractor and/or its mounted or trailed equipment. If you notice degradation of performance, contact your dealer for assistance. He may have useful information for improvements, or a kit may be available to enhance the performance.

- Do not use the tractor for another purpose than intended by the manufacturer and outlined in this manual.
- Do not use the tractor beyond its limits of terrain gradient and stability as outlined further in this manual. Using the tractor beyond these limits may result in roll-over or tip-over. Observe the recommendations in this manual.
- Do not use the tractor on higher speeds than allowed by the load and the environment. A wet surface or other low adherence conditions may increase the braking distance or result in vehicle instability. Always adapt your traveling speed according to the load of the vehicle and the characteristics of the road.
- Do not use the tractor near or on soft verges of canals and brooks or banks and verges that are undermined by rodents. The tractor may sink sideways and rollover.
- Do not use the tractor on brittle bridge heads and poor bridge floors. These constructions may collapse and cause roll-over of the tractor. Always check out the condition and carrying capacity of bridges and ramps prior to engage.
- Do not use the tractor without wearing the seat restraint system during activities where roll-over or tip-over hazards exist. The ROPS cab or ROPS structure will only be fully effective when the driver remains attached to his seat.
- Do not use equipment mounted on the tractor which is not correctly matching and firmly fixed. Such equipment may increase the risk for roll-over and hit the tractor when coming loose. Ensure that the dimensions of the three-point linkage interface of both the tractor and the equipment are matching according to the categories defined in ISO 730. Ensure that the dimensions and speed of the PTO shaft on the tractors are matching those of the equipment.
- Do not use the tractor in combination with equipment, without having consulted the specific Operators Manual provided with the equipment. The tractor is a universal

- tool to carry, tow, and drive a variety of equipment. This manual alone cannot provide you with all the information required for the safe operation of the combination.
- Do not use the tractor beyond its limits of dynamic stability. High speed, abrupt maneuvers, and fast and short cornering will increase the risk of roll-over.
- Do not use the tractor for pulling work, in cases where you do not know whether the load will yield, for instance when pulling stumps. The tractor may flip over when the stump is not yielding.
- Be extremely cautious when working with the tractor on forage silos without lateral concrete walls. Dual wheels or a wide track setting may improve the lateral stability of the tractor.
- Be cautious that the center of gravity of the tractor may increase when loads on the front-end loader or the three-point linkage are raised. In these conditions, the tractor may roll-over earlier than expected.
- Do not step down from the tractor without shutting down the PTO, shifting the transmission to park or neutral and applying the park brake, unless continued PTO operation is required for some equipment, such as pumps or wood chippers. The latter equipment may have an emergency stop device on the equipment itself, as human intervention is needed during operation. But other equipment, engaged and driven by the tractor will have no means to stop the power transmission, other than the PTO clutch of the tractor.
- You shall take the necessary precautions to always be aware of the possible presence of bystanders, certainly when maneuvering in confined areas, such as the farm yard and sheds. Keep people away from the tractor duringwork; ask bystanders to leave the field. There is not only the risk to be overrun by the tractor, but objects ejected by some equipment mounted on the tractor, such as a rotary mower, may cause harm. Stones may be thrown further than the mowed crop. Pay the necessary attention while operating next to public roads or footpaths. Thrown objects can get projected outside the field and hit unprotected people like bikers or pedestrians. Wait to cut the edge of the field till it is clear of bystanders.
- Do not allow riders on the tractor; do not allow people standing on the access way or step to the cab when the tractor is moving. Your view to the left will be obstructed and a rider risks to fall from the tractor during unforeseen or abrupt movements.
- Always stay clear from implements operating area and especially do not stand between tractor and trailed vehicle either three-point linkage when operating lift controls; ensure no bystanders are near these operating areas.
- Certain functions of your tractor, if equipped with a CVT transmission, are controlled by software and some of them are safety related. Do not attempt to modify or download software from spurious sources. Settings

and logics may be destroyed and affect seriously the function of the tractor. This may result in unpredictable and unsafe behavior of the tractor. Only your dealer is entitled to intervene on the software of the tractor. He has the appropriate tools and data sets for it and owns the officially released software versions and updates for your tractor.

- Your tractor may be equipped with a number of sensors to control safety functions. Tripping these sensors will result in a safe operation mode. Do not attempt to bypass any function on the tractor. You will be exposed to serious hazards, and moreover, the behavior of the tractor may become unpredictable.
- A tractor has only one operator station and is a one man operated vehicle. Other people on or around the tractor during normal operation are not allowed.
- The machine is designed and produced exclusively for agricultural use.
- The machine is not designed for light/heavy forestry applications; usage is prohibited for forestry applications.
- All other use will be considered to be contrary to the use specified by CNH AMERICA LLC, who cannot be held liable for damage to property or the machine, or for personal injuries which may result.
- Persons who risk improper use will therefore assume the responsibility for any consequences arising from such use.
- Compliance with the instructions for use, maintenance and repairs described in this manual, are the essential

- preconditions for the use specified by CNH AMERICA LLC.
- The machine must only be used, serviced, or repaired by personnel trained in the relevant working methods and safety regulations and who have been authorized to work on the machine.
- The user must also observe the rules concerning general safety and accident prevention, including the Highway Code when driving on public highways.
- Any arbitrary modifications made to this machine will release CNH AMERICA LLC from any liability resulting from damage or injury.
- CNH AMERICA LLC and all its distribution organizations, inclusive of, but not restricted to, national, regional, or local distributors, cannot be held liable for damage resulting from the malfunction of parts and/or components not approved by CNH AMERICA LLC.
- Under no circumstances will a guarantee be issued for products made or sold by CNH AMERICA LLC that are damaged as a result of the malfunction of parts and/or components not approved by CNH AMERICA LLC.
- The use of biodiesel blends meeting Specification Standards ASTM 6751 or EN14214 are approved for your engine up to B5 (5% blend ratio). It is highly recommended to use biodiesel fuel from accredited suppliers to maintain quality and consistency of the fuel.

Electro-Magnetic Compatibility (EMC)

This machine complies strictly with the European Regulations on electro-magnetic emissions. However, interference may arise as a result of add-on equipment which may not necessarily meet the required standards. As such interference can result in serious malfunction of the unit and/or create unsafe situations, you must observe the following:

- Ensure that each piece of non- NEW HOLLAND equipment fitted to the machine bears the CE mark.
- The maximum power of emission equipment (radio, telephones, etc.) must not exceed the limits imposed by the national authorities of the country where you use the machine.
- The electro-magnetic field generated by the add-on system should not exceed 24 V/m at any time and at any location in the proximity of electronic components.

Failure to comply with these rules will render the NEW HOLLAND warranty null and void.

Manual scope

This manual gives information for use of this tractor, as intended and under the conditions foreseen by the manufacturer during normal operation and routine service and maintenance.

- Normal operation means the use of the tractor for the purpose intended by the manufacturer by an operator familiar with the tractor and the mounted or towed equipment and complying with the information for operation and safe practices, as specified by the manufacturer in this manual and by the signs on the tractor and the equipment.
- Normal operation includes the preparation and storage of the tractor, swinging components into work position and vice versa, adding or removing ballast and picking up and setting off attachments.
- Normal operation includes the adjustment and setting of the tractor and equipment, for the specific condition of the field and/or the crop.
- Routine service and maintenance means activities that must be done daily by an operator familiar with the tractor characteristics and complying with the information for routine service and safe practices, as specified by the manufacturer in this manual and by signs on the tractor, in order to maintain its proper function. Routine service includes activities such as fueling, cleaning, washing, topping up fluid levels, greasing, replacing of consumable articles such as lamp bulbs.
- This manual does not give all the information related to periodical service, converting and repairs to be car-

- ried out by professional service personnel. For some of the latter activities, there may be a need for appropriate facilities, technical skills and tools which are not supplied with the tractor, please refer to your dealer or authorized workshop.
- Periodical service means activities that must be done at defined intervals by trained personnel familiar with the tractor characteristics and which are complying with the information for periodical service and safe practices, as partly specified by the manufacturer in this manual and in other Company literature, in order to maintain the expected life time of the tractor.
- Converting means activities that must be done by professional service personnel familiar with the tractor characteristics and complying with the information for converting, as partly specified by the manufacturer in this manual, in assembly instructions or other Company literature, in order to fit the tractor to a specific configuration.
- Repair means activities that must be done by professional service personnel only familiar with the tractor characteristics and complying with the information for repair, as specified by the manufacturer in the dealer's workshop manual, in order to restore the proper function of the tractor after a failure or degradation of performance.

Metric and Imperial units abbreviations

Typical applications	Metric unit		Imperial unit	
	Name	Symbol	Name	Symbol
Area (Land area)				
	hectare	ha	acre	ac
	square meter	m²	square foot	ft²
		_	square inch	in²
	square millimeter	mm²	square inch	in²
Electricity				
	ampere	Α	ampere	A
	volt	V	volt	V
	microfarad	μF	microfarad	μF
	ohm	Ω	ohm	Ω
Force				
	kilonewton	kN	pound	lb
	newton	N	pound	lb
Force per length				
	newton per meter	N/m	pound per foot	lb/ft
1			pound per inch	lb/in
Frequency				
	megahertz	MHz	megahertz	MHz
	kilohertz	kHz	kilohertz	kHz
	hertz	Hz	hertz	Hz
Frequency - Rotational			•	
	revolution per minute	r/min	revolution per minute	r/min ^a
	·	rpm	·	rpm
Length		<u> </u>	•	
	kilometer	km	mile	mi
	meter	m	foot	ft
	centimeter	cm	inch	in
	millimeter	mm	inch	in
	micrometer	μm		
Mass			•	
	kilogram	kg	pound	lb
	gram	g	ounce	OZ
	milligram	mg		
Mass per mass			•	
•	milligram per kilogram	mg/ kg	parts per million	ppm
Power		<u> </u>		
	kilowatt	kW	horsepower	Нр
	watt	W	Btu per hour	Btu/hr
	au	• •	Btu per minute	Btu/min
Pressure or stress (Force	ner area)		Did pol filliato	20,11111
	kilopascal	kPa	pound per square inch	psi
	Клораоба	i i i	inch of mercury	inHg
	pascal	Pa	inch of water	inH2O
	•	MPa		
	megapascal		pound per square inch	psi
	millibar	mbar	+	
	bar	bar		

Typical applications	Metric unit		Imperial unit	
	Name	Symbol	Name	Symbol
Temperature (other than the				
	degrees Celsius	°C	degrees Fahrenheit	°F
Time				
	hour	h	hour	h
	minute	min	minute	min
	second	S	second	S
Torque (includes bending n	noment, moment of force, an			
	newton meter	N m	pound foot	lb ft
			pound foot	lb in
Velocity				
	kilometer per hour	km/h	mile per hour	mph
	meter per second	m/s	foot per second	ft/s
	millimeter per second	mm/s	inch per second	in/s
	meter per minute	m/min	foot per minute	ft/min
Volume (includes capacity)				
	cubic meter	m³	cubic yard	yd³
				cu yd
	liter	I	cubic inch	in³
	liter	I	US gallon	US gal
			UK gallon	UK gal
			US quart	US qt
			UK quart	UK qt
	milliliter	ml	fluid ounce	fl oz
Volume per time (includes	discharge and flow rate)			
	cubic meter per minute	m³/min	cubic foot per minute	ft³/min
	liter per minute	l/min	US gallon per minute	US gal/min
	milliliter per minute	ml/min	UK gallon per minute	UK gal/min
Sound power level and sou				
·	decibel	dB	decibel	dB
Water hardness				
	German hardness	°dH	English hardness	°e
	French hardness	°fH	parts per million	ppm

Glossary

Acronym	Definition
DEF	Diesel Exhaust Fluid
ISO	International Organization for Standardization
MSDS	Material Safety Data Sheet
NOx	Nitrogen Oxide
PPE	Personal Protective Equipment
SCR	Selective Catalytic Reduction
ULSD	Ultra Low Sulfur Diesel
%	Percent
<	Less than
>	Greater than

Thank you so much for reading. Please click the "Buy Now!" button below to download the complete manual.



After you pay.

You can download the most perfect and complete manual in the world immediately.

Our support email: ebooklibonline@outlook.com