

ORIGINAL INSTRUCTIONS - according to Regulation (EU) 2018/985, Annex II

OPERATOR'S MANUAL

Boomer™ 40

Boomer™ 50

With ROPS

*Boomer™ 40 ROPS - PIN LSM0B40RCJLC10144 and above;
From PIN LSM0B40RxHLC10001 to LSM0B40RCJLC10143*

*Boomer™ 50 ROPS - PIN LSM0B50RCJLC10561 and above;
From PIN LSM0B50RxHLC10001 to LSM0B50RCJLC10560*

Boomer™ 40

Boomer™ 50

With Cab

Boomer™ 40 Cab - PIN LSM0B40CxHLC10001 and above

*Boomer™ 50 Cab - PIN LSM0B50CAJLC10333 and above;
From PIN LSM0B50CxHLC10001 to LSM0B50CAJLC10332*

Stage IIIA

With Hydrostatic Transmission (HST) and Mechanical Transmission

Compact Tractor

Part number 51559578

3rd edition English

March 2019

Replaces part number 51559530



Contents

1 GENERAL INFORMATION

Note to the owner.....	1-1
Intended use.....	1-4
Electro-Magnetic Compatibility (EMC)	1-6
Manual scope and required training level	1-7
Metric and Imperial units abbreviations	1-9
Product Identification Number (PIN).....	1-11
Product Identification Number (PIN) (Cab)	1-13
Operator's manual storage	1-15
Machine orientation - Roll Over Protective Structure (ROPS).....	1-16
Machine orientation - Cab	1-17

2 SAFETY INFORMATION

Safety alert symbol and signal word definition	2-1
Safety rules.....	2-2
Starting the machine	2-14
Parking the machine.....	2-16
Ecology and the environment	2-17
Safety aspects in accordance with Regulation (EU) 1322/2014 - Annex XXII and subsequent amendments and modifications	2-18
Safety features - Roll Over Protective Structure (ROPS)	2-27
Safety features - Cab	2-29
Tractor jacking points.....	2-30
Airborne noise emission - Roll Over Protective Structure (ROPS)	2-31
Airborne noise emission - Cab	2-31
Exhaust emission levels.....	2-32
Vibration levels - Roll Over Protective Structure (ROPS)	2-33
Vibration levels - Cab	2-34
Machine stability.....	2-35
Emergency exit	2-38
Safety signs - Roll Over Protective Structure (ROPS)	2-39
Safety signs - Cab	2-49
Instructional signs - Roll Over Protective Structure (ROPS)	2-59
Instructional signs - Cab	2-71
International symbols.....	2-83

3 CONTROLS AND INSTRUMENTS

ACCESS TO OPERATOR'S PLATFORM

Cab door.....	3-1
Cab side window	3-2
Cab rear window	3-2

OPERATOR'S SEAT

Seat belt	3-3
Seat controls	3-4

Roll Over Protective Structure (ROPS) - Rear mounted	3-5
Roll Over Protective Structure (ROPS) - Mid-mounted.....	3-7

FORWARD CONTROLS

Instrument cluster - Identification	3-9
Cruise control.....	3-11
Transmission shuttle shift lever.....	3-12
Clutch pedal	3-12
Brake pedals	3-13
Foot throttle pedal	3-14
Hand throttle lever	3-15
Horn switch	3-15
Stationary Power Take-Off (PTO) switch	3-16
Hazard light switch	3-17
Power Take-Off (PTO) switch.....	3-18
Key switch	3-19
Differential lock pedal.....	3-20
Hydrostatic Transmission (HST) control pedals	3-21
Tilt steering lever	3-21
Multifunction light switch.....	3-22
Creeper speed selection lever.....	3-23

LEFT-HAND SIDE CONTROLS

Transmission range lever.....	3-24
Park brake - Roll Over Protective Structure (ROPS).....	3-24
Front-wheel drive lever	3-25
Mid Power Take-Off (PTO) lever - Optional	3-26
Rear Power Take-Off (PTO) speed selection lever.....	3-26
Ground Speed Power Take-Off (GSP) shift lever	3-27

RIGHT-HAND SIDE CONTROLS

Park brake - Cab	3-28
Hydraulic Power Lift (HPL) - Roll Over Protective Structure (ROPS)	3-29
Hydraulic Power Lift (HPL) - Cab.....	3-30
Draft control - Roll Over Protective Structure (ROPS)	3-31
Draft control - Cab	3-32
Rear remote control valves - Roll Over Protective Structure (ROPS).....	3-33
Rear remote control valves - Cab	3-34
Mid mount two spool control valve - Roll Over Protective Structure (ROPS) - Optional.....	3-35
Mid mount two spool control valve - Cab - Optional.....	3-37
Transmission main shift lever.....	3-39
Hydrostatic Transmission (HST) range lever	3-40
Beacon switch	3-41
Cab internal lighting	3-41
Cab external lighting	3-42
Front window wiper and washer.....	3-43
Rear window wiper and washer - Optional	3-44
Auxiliary power outlet.....	3-45

OVERHEAD CONTROLS

Cab climate control	3-46
Air conditioning - Adjust	3-47
Front sun shade	3-51
Rear-view inside mirror	3-51

EXTERIOR CONTROLS

Rear-view outside mirrors	3-52
Hood release latch	3-52

4 OPERATING INSTRUCTIONS

COMMISSIONING THE UNIT

Engine break-in procedure	4-1
Power Take-Off (PTO) operation	4-2
Ground Speed Power Take-Off (GSP) operation	4-5
Three-point hitch	4-8
Attaching three-point equipment	4-9
Extendable drawbar	4-12
Top link	4-13
Hydraulic Power Lift (HPL) drop rate control valve	4-13

STARTING THE UNIT

Key switch	4-14
Cold starting aids	4-15
Starting the engine	4-16
Operator presence system	4-20
Starting the tractor with jumper cables	4-21

STOPPING THE UNIT

Stopping the engine	4-22
Emergency stopping	4-23
Mechanical service brakes - Roll Over Protective Structure (ROPS)	4-24
Mechanical service brakes - Cab	4-26

MOVING THE UNIT

Steering wheel adjustment	4-28
Steering operation	4-30
Transmission operation at low ambient temperatures	4-31
Hydrostatic Transmission (HST) operation	4-32
Mechanical transmission operation	4-34
Creeper speed operation	4-36

PARKING THE UNIT

Parking the machine - Roll Over Protective Structure (ROPS)	4-38
Parking the machine - Cab	4-40

5 TRANSPORT OPERATIONS

ROAD TRANSPORT

External lighting - Roll Over Protective Structure - (ROPS)	5-1
External lighting - Cab	5-2
Hazard warning lights - Operation - Roll Over Protective Structure (ROPS)	5-3
Hazard warning lights - Operation - Cab	5-4
Turn signal - Operation	5-5
Road lights - Operation - Roll Over Protective Structure (ROPS)	5-7
Road lights - Operation - Cab	5-8
Work lights - Operation - Roll Over Protective Structure (ROPS)	5-9
Work lights - Operation - Cab	5-10
Rear work light - Operation - Roll Over Protective Structure (ROPS)	5-11
Rear work lights - Operation - Cab	5-12
Driving the vehicle	5-13

SHIPPING TRANSPORT

Carrying the tractor on a transporter	5-14
---	------

RECOVERY TRANSPORT

Towing the tractor for recovery	5-14
---------------------------------------	------

6 WORKING OPERATIONS

GENERAL INFORMATION

Tractor ballasting	6-1
Tractor ballasting weights	6-2
Liquid ballast	6-3

7 MAINTENANCE

GENERAL INFORMATION

General information	7-1
Battery disconnect switch	7-2
General specification - Diesel fuel	7-3
Biodiesel fuel	7-4
Refueling the tractor - Roll Over Protective Structure (ROPS)	7-6
Refueling the tractor - Cab	7-7
Change engine coolant to Organic Acid Technology (OAT) coolant	7-8
Consumables	7-10
Torque - Minimum tightening torques for normal assembly	7-11

MAINTENANCE CHART

Maintenance chart	7-16
-------------------------	------

Every 10 hours or daily

Engine oil level - Check	7-18
Engine cooling system - Check	7-19

After the first 50 hours of operation

Engine oil and oil filter - Change	7-20
Fuel filter - Change	7-21
Hydraulic oil filter - Replace	7-21
Hydrostatic Transmission (HST) oil filter - Replace	7-23
Roll Over Protective Structure (ROPS) frame - Check	7-24
Wheel bolt / nut - Tighten	7-25

Every 50 hours

Grease fittings	7-26
Transmission fluid level - Check	7-27
Clutch pedal free play - Check	7-27
Brake pedal free play - Check	7-29
Hydrostatic Transmission (HST) neutral position - Check and Adjustment	7-30
Fan belt tension - Check	7-31
Wheels and tires pressure - Check	7-32
Front axle and differential oil level - Check	7-34
Air cleaner - Clean	7-35
Cab air filter - Check and cleaning	7-37

Every 100 hours

Fuel filter-Drain	7-38
-------------------------	------

Every 300 hours

Engine lubrication system - Change fluid	7-39
Hydraulic oil filter - Replace	7-39
Hydrostatic Transmission (HST) oil filter - Replace	7-39
Fuel filter - Change	7-39
Engine belts - Adjust	7-39
Roll Over Protective Structure (ROPS) - Check	7-41
Wheels bolt/nut	7-42
Front wheels toe-in	7-42
Air cleaner primary element - Replace	7-43

Every 500 hours

Cab air filter - Replace	7-44
--------------------------------	------

Every 600 hours

Front axle differential oil - Change fluid	7-45
Transmission fluid - Change	7-47

Every 1000 hours

Air cleaner inner element - Replace	7-48
Engine coolant - Draining and flushing	7-49

General maintenance

Fuel injection system - Bleed	7-50
Hydrostatic transmission control components - Adjust – Neutral	7-52
Engine belts - Adjust	7-54
Battery	7-55
Alternator	7-56
Fuses	7-57
Maxi fuse	7-60
Headlight	7-61
Tail/brake light bulb	7-62
Front turn signal/hazard light bulb	7-64
Wheels bolt/nut tighten	7-67
Brake pedal free play - Adjust	7-68
Clutch pedal free play - Adjust	7-69

STORAGE

Storage of tractor	7-70
Removal of tractor from storage	7-72

8 TROUBLESHOOTING

SYMPTOM(S)

Engine - Troubleshooting	8-1
Clutch - Troubleshooting	8-2
Hydraulic service brakes - Troubleshooting	8-2
Hydraulic lift system - Troubleshooting	8-2
Steering - Troubleshooting	8-3
Hydrostatic transmission - Troubleshooting	8-3
Electrical system - Troubleshooting	8-4

9 SPECIFICATIONS

Wheel tread settings	9-1
Tire pressures and permissible loads	9-2
General specifications	9-3
Tractor dimensions - Roll Over Protective Structure (ROPS)	9-10
Tractor dimensions - Cab	9-13

10 ACCESSORIES

Optional equipment	10-1
--------------------------	------

11 FORMS AND DECLARATIONS

Delivery report - Owner Copy	11-3
Delivery report - Dealer Copy	11-5

1 - GENERAL INFORMATION

Note to the owner

Introduction

Thank you for purchasing this NEW HOLLAND product

All of us here at NEW HOLLAND welcome you as an appreciated and valued customer. We trust that the design of this machine will fulfill your needs and expectations in performance, service, and providing you with many years of safe and satisfying performance.

You have purchased a dependable machine and by properly maintaining, servicing, and operating this machine you can expect to receive the performance and long service built into this machine.

Operator's manual

Please have all operators read this manual carefully and keep this manual available for ready reference. Read this manual to make sure that you have a complete understanding of how to operate this machine safely, correctly, and for the most effective performance of the machine.

NOTE: *This operator's manual may be available in other languages; see your NEW HOLLAND dealer for ordering.*

This manual contains important information concerning the adjustment and maintenance of your new equipment.

NOTE: *Some images of the machine in this manual may differ slightly in some detail. Any variations will be similar enough for you to understand the information or instructions.*

Throughout this operator's manual, references to the right-hand and left-hand sides of the machine are determined by facing the forward operating direction of travel.



This is the safety alert symbol. The safety alert symbol alerts you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible death or injury.

⚠ WARNING

Illustrations in this manual may show protective shielding open or removed to better illustrate a particular feature or adjustment.

Replace all shields before operating the machine.

Failure to comply could result in death or serious injury.

W0012A

Your NEW HOLLAND dealer and service

Your NEW HOLLAND dealer has performed a pre-delivery setup, inspection, and testing to make sure that your machine operates at its best performance level.

Your NEW HOLLAND dealer will instruct you in the general operation of your new equipment. (Refer to the 'Delivery Report' at the back of this manual.) Your dealer's staff of factory-trained service technicians will be glad to answer any questions that may arise regarding the operation of your machine.

Your NEW HOLLAND dealer carries a complete line of genuine NEW HOLLAND service parts. These parts are manufactured and carefully inspected to ensure high quality and accurate fitting of any necessary replacement parts. Be prepared to give your dealer the model and product identification number of your new equipment when ordering parts. Locate these numbers now and record them below. Refer to the 'General Information' section of this manual for the location of the model and product identification numbers of your machine.

PLEASE RECORD THE FOLLOWING INFORMATION

Model

Product Identification Number (PIN)

Date Purchased

Engine Model (As Applicable)

Engine PIN (As Applicable)

ATTENTION: *The engine and fuel system on your machine is designed and built to government emission standards. Tampering by dealer, customers, operators, and end users is strictly prohibited by law. Failure to comply could result in government fines, rework charges, invalid warranty, legal action, and possible confiscation of the machine until rework to original condition is completed. Engine service and/or repairs must be done by a certified technician only!*

Improvements

CNH Industrial America LLC is continually striving to improve its products. We reserve the right to make improvements or changes when improvements or changes become practical and possible to do so, without incurring any obligation to make changes or additions to the equipment sold previously.

Intended use

INTENDED USE OF YOUR TRACTOR

Your tractor is designed and made to pull, to carry, and to power a variety of mounted or towed equipment, although within some physical limits. The working speed and performance may depend on a number of various parameters, such as weather and terrain conditions. Though the tractor is designed to perform in combination with a variety of equipment in most crops and conditions, there may be a number of combinations of above parameters, for which there is severe degradation of performance of the tractor and/or its mounted or trailed equipment. If you notice degradation of performance, contact your dealer for assistance. He may have useful information for improvements, or a kit may be available to enhance the performance.

- Do not use the tractor for another purpose than intended by the manufacturer and outlined in this manual.
- Do not use the tractor beyond its limits of terrain gradient and stability as outlined further in this manual. Using the tractor beyond these limits may result in roll-over or tip-over. Observe the recommendations in this manual.
- Do not use the tractor on higher speeds than allowed by the load and the environment. A wet surface or other low adherence conditions may increase the braking distance or result in vehicle instability. Always adapt your traveling speed according to the load of the vehicle and the characteristics of the road.
- Do not use the tractor near or on soft verges of canals and brooks or banks and verges that are undermined by rodents. The tractor may sink sideways and roll-over.
- Do not use the tractor on brittle bridge heads and poor bridge floors. These constructions may collapse and cause roll-over of the tractor. Always check out the condition and carrying capacity of bridges and ramps prior to engage.
- Do not use the tractor without wearing the seat restraint system during activities where roll-over or tip-over hazards exist. The ROPS cab or ROPS structure will only be fully effective when the driver remains attached to his seat.
- Do not use equipment mounted on the tractor which is not correctly matching and firmly fixed. Such equipment may increase the risk for roll-over and hit the tractor when coming loose. Ensure that the dimensions of the three-point linkage interface of both the tractor and the equipment are matching according to the categories defined in ISO 730. Ensure that the dimensions and speed of the PTO shaft on the tractors are matching those of the equipment.
- Do not use the tractor in combination with equipment, without having consulted the specific Operators Manual provided with the equipment. The tractor is a universal tool to carry, tow, and drive a variety of equipment. This manual alone cannot provide you with all the information required for the safe operation of the combination.
- Do not use the tractor beyond its limits of dynamic stability. High speed, abrupt maneuvers, and fast and short cornering will increase the risk of roll-over.
- Do not use the tractor for pulling work, in cases where you do not know whether the load will yield, for instance when pulling stumps. The tractor may flip over when the stump is not yielding.
- Be extremely cautious when working with the tractor on forage silos without lateral concrete walls. Dual wheels or a wide track setting may improve the lateral stability of the tractor.
- Be cautious that the center of gravity of the tractor may increase when loads on the front-end loader or the three-point linkage are raised. In these conditions, the tractor may roll-over earlier than expected.
- Do not step down from the tractor without shutting down the PTO, shifting the transmission to park or neutral and applying the park brake, unless continued PTO operation is required for some equipment, such as pumps or wood chippers. The latter equipment may have an emergency stop device on the equipment itself, as human intervention is needed during operation. But other equipment, engaged and driven by the tractor will have no means to stop the power transmission, other than the PTO clutch of the tractor.
- You shall take the necessary precautions to always be aware of the possible presence of bystanders, certainly when maneuvering in confined areas, such as the farm yard and sheds. Keep people away from the tractor during work; ask bystanders to leave the field. There is not only the risk to be overrun by the tractor, but objects ejected by some equipment mounted on the tractor, such as a rotary mower, may cause harm. Stones may be thrown further than the mowed crop. Pay the necessary attention while operating next to public roads or footpaths. Thrown objects can get projected outside the field and hit unprotected people like bikers or pedestrians. Wait to cut the edge of the field till it is clear of bystanders.
- Do not allow riders on the tractor; do not allow people standing on the access way or step to the cab when the tractor is moving. Your view to the left will be obstructed and a rider risks to fall from the tractor during unforeseen or abrupt movements.
- Always stay clear from implements operating area and especially do not stand between tractor and trailed vehicle either three-point linkage when operating lift controls; ensure no bystanders are near these operating areas.
- Certain functions of your tractor, if equipped with a CVT transmission, are controlled by software and some of them are safety related. Do not attempt to modify or download software from spurious sources. Settings

and logics may be destroyed and affect seriously the function of the tractor. This may result in unpredictable and unsafe behavior of the tractor. Only your dealer is entitled to intervene on the software of the tractor. He has the appropriate tools and data sets for it and owns the officially released software versions and updates for your tractor.

- Your tractor may be equipped with a number of sensors to control safety functions. Tripping these sensors will result in a safe operation mode. Do not attempt to bypass any function on the tractor. You will be exposed to serious hazards, and moreover, the behavior of the tractor may become unpredictable.
- A tractor has only one operator station and is a one man operated vehicle. Other people on or around the tractor during normal operation are not allowed.
- The machine is designed and produced exclusively for agricultural use.
- The machine is not designed for light/heavy forestry applications; usage is prohibited for forestry applications.
- All other use will be considered to be contrary to the use specified by CNH AMERICA LLC, who cannot be held liable for damage to property or the machine, or for personal injuries which may result.
- Persons who risk improper use will therefore assume the responsibility for any consequences arising from such use.
- Compliance with the instructions for use, maintenance and repairs described in this manual, are the essential

preconditions for the use specified by CNH AMERICA LLC.

- The machine must only be used, serviced, or repaired by personnel trained in the relevant working methods and safety regulations and who have been authorized to work on the machine.
- The user must also observe the rules concerning general safety and accident prevention, including the Highway Code when driving on public highways.
- Any arbitrary modifications made to this machine will release CNH AMERICA LLC from any liability resulting from damage or injury.
- CNH AMERICA LLC and all its distribution organizations, inclusive of, but not restricted to, national, regional, or local distributors, cannot be held liable for damage resulting from the malfunction of parts and/or components not approved by CNH AMERICA LLC.
- Under no circumstances will a guarantee be issued for products made or sold by CNH AMERICA LLC that are damaged as a result of the malfunction of parts and/or components not approved by CNH AMERICA LLC.
- The use of biodiesel blends meeting Specification Standards ASTM 6751 or EN14214 are approved for your engine up to B5 (5% blend ratio). It is highly recommended to use biodiesel fuel from accredited suppliers to maintain quality and consistency of the fuel.

Electro-Magnetic Compatibility (EMC)

This machine complies strictly with the European Regulations on electro-magnetic emissions. However, interference may arise as a result of add-on equipment which may not necessarily meet the required standards. As such interference can result in serious malfunction of the unit and/or create unsafe situations, you must observe the following:

- Ensure that each piece of non- NEW HOLLAND equipment fitted to the machine bears the CE mark.
- The maximum power of emission equipment (radio, telephones, etc.) must not exceed the limits imposed by the national authorities of the country where you use the machine.
- The electro-magnetic field generated by the add-on system should not exceed **24 V/m** at any time and at any location in the proximity of electronic components.

Failure to comply with these rules will render the NEW HOLLAND warranty null and void.

Manual scope and required training level

Introduction to this manual

This manual gives information about the use of your NEW HOLLAND machine as intended and under the conditions foreseen by NEW HOLLAND during normal operation, routine service, and maintenance.

This manual does not contain all the information that relates to periodic service, conversions, and repairs that only trained service personnel can perform. Some of these activities may require appropriate facilities, technical skills, and/or tools that NEW HOLLAND does not supply with the machine.

The manual contains the chapters as shown on the Contents pages. See the Index at the end of this manual to locate specific items about your NEW HOLLAND machine.

Normal operation

Normal operation consists of the use of this machine for the purpose NEW HOLLAND intends by an operator that:

- Is familiar with the machine and any mounted equipment or towed equipment
- Complies with the information on operation and safe practices as specified by NEW HOLLAND in this manual and by the signs on the machine

Normal operation includes:

- Preparation and storage of the machine
- Addition and removal of ballast
- Connection and disconnection of mounted equipment and/or towed equipment
- Adjustment and configuration of the machine and equipment for the specific conditions of the job site, field, and/or crop
- Movement of components into and out of working positions

Routine service and maintenance

Routine service and maintenance consists of the daily activities necessary to maintain the proper machine function. The operator must:

- Be familiar with the machine characteristics
- Comply with the information on routine service and safe practices as specified by NEW HOLLAND in this manual and by the signs on the machine

Routine service can include:

- Fueling
- Cleaning
- Washing
- Topping up fluid levels

- Greasing
- Replacing consumable items such as light bulbs

Periodic service, conversions, and repairs

Periodic service consists of activities that are necessary to maintain the expected life of the NEW HOLLAND machine. These activities have defined intervals.

Trained service personnel familiar with the machine characteristics must perform these activities at the defined intervals. Trained service personnel must comply with the information on periodic service and safe practices as partly specified by NEW HOLLAND in this manual and/or other company literature.

Periodic service includes:

- Oil change service for the engine, hydraulic circuits, or transmission
- Periodic exchange of other substances or components as required

Conversion activities rebuild the NEW HOLLAND machine in a configuration that is appropriate for a specific job site, crop, and/or soil conditions (e.g., installation of dual wheels). Conversion activities must be done:

- By trained service personnel familiar with the machine characteristics
- By trained service personnel that comply with the information on conversion as partly specified by NEW HOLLAND in this manual, assembly instructions, and/or other company literature

Repair activities restore proper function to a NEW HOLLAND machine after a failure or degradation of performance. Dismantling activities occur during the scrapping and/or dismantling of the machine.

Trained service personnel familiar with the machine characteristics must perform these activities. Trained service personnel must comply with the information for repair as specified by NEW HOLLAND in the service manual.

Before you operate

Read this manual before you start the engine or operate this NEW HOLLAND machine. Contact your NEW HOLLAND dealer if:

- You do not understand any information in this manual
- You need more information
- You need assistance

All persons training to operate, or who will operate this NEW HOLLAND machine should be old enough to possess a valid local vehicle operating permit (or meet other applicable local age requirements). These persons must

Thank you so much for reading.
Please click the “Buy Now!”
button below to download the
complete manual.



After you pay.

You can download the most
perfect and complete manual in
the world immediately.

Our support email:

ebooklibonline@outlook.com