

ORIGINAL INSTRUCTIONS

OPERATOR'S MANUAL

T5.90

T5.100

T5.110

Electro Command™ S

Tractor

Part number 51599081

1st edition English
February 2019



Contents

1 GENERAL INFORMATION

Note to the Owner	1-1
Safety rules	1-3
Product identification	1-4
Advice	1-6
Electronic modules - Definition	1-7
Note to the Owner	1-8
International symbols	1-10
Product identification	1-12
Product identification	1-14
Advice	1-15

2 SAFETY INFORMATION

Safety rules	2-1
Safety rules	2-2
Safety rules - General information	2-3
Safety rules – Maintenance	2-4
Safety rules - Wheels and tires	2-5
Safety rules – Explosions and fires	2-6
Safety rules - Fire extinguisher	2-7
Safety rules – Battery	2-8
Safety rules - Passenger seat	2-9
Safety rules – Operator presence system	2-9
Safety rules - Power Take-Off (PTO)	2-10
Safety rules - Reflectors and warning lights	2-11
Safety rules - Seat belts	2-12
Safety rules - Operator protective structure	2-13
Safety rules - HVAC system	2-15
Safety rules - Personal Protective Equipment (PPE)	2-16
Safety rules - "Do not use" sign	2-17
Safety rules - Hazardous chemicals	2-18
Safety rules - Near utilities	2-19
Safety rules - In the event of electrical storms	2-20
Safety rules – Mounting and dismounting the machine	2-21
Safety rules - Lifting and overhead loads	2-22
Safety rules - Front end loader	2-23
Foreword	2-24
Foreword	2-25
Noise level	2-33
Personal safety	2-34
General specification	2-35
Safety rules	2-38
Platform, cab, bodywork, and decals - Personal safety	2-39
Personal safety	2-40
Safety - Basic instructions	2-41
Safety signs	2-42

3 CONTROLS AND INSTRUMENTS

Access to operator's platform

Cab - Access/Exit	3-1
Cab and platform - Localization overview	3-2
Rear-view outside mirrors - Localization overview	3-4

Operator's seat

Operator seat - Adjust	3-5
Pneumatically-adjusted operator seat - Adjust "DELUXE" model	3-6
Seat restraints - Localization overview	3-8

Passenger seat

Passenger's seat	3-9
------------------------	-----

Forward controls

Instrument cluster - Localization overview	3-9
Cab controls - Control identification	3-14

Left-hand side controls

Console Left-hand console - Localization overview	3-17
Hand brake lever - Operating	3-18

Right-hand side controls

Pillar trim plate - Localization overview	3-19
Cab right-hand side panel - Localization overview	3-21
Air conditioning - Operating	3-23
Parking lock external controls - Operating	3-25

Exterior controls

Cab controls - Control identification	3-26
---	------

DISPLAY SETTINGS

Instrument cluster Analog-Digital Instrument Cluster (ADIC) - Program	3-27
Instrument cluster Analog-Digital Instrument Cluster (ADIC) - Program	3-31
Instrument cluster - Program	3-32
Instrument cluster - Program	3-34
Instrument cluster - Program	3-37
Instrument cluster - Program	3-38
Instrument cluster - Program	3-40
Instrument cluster - Program	3-41
Instrument cluster - Program	3-42
Instrument cluster - Basic instructions	3-43

4 OPERATING INSTRUCTIONS

Commissioning the unit

Engine - Safety rules	4-1
Fuel tank - Fill	4-2

Starting the unit

Engine starting system - Start	4-3
--------------------------------------	-----

Stopping the unit

Engine starting system - Stop	4-5
Mechanical battery isolator - Operating	4-6

Moving the unit

Engine starting system - Start	4-7
Engine - Operating	4-8

5 TRANSPORT OPERATIONS

Road transport

Frame - Start	5-1
---------------------	-----

Recovery transport

Drawbars and towing hitches - Tow	5-1
Brakes and controls - Secure.....	5-3

6 WORKING OPERATIONS

General information

Front-Wheel Drive (FWD) engagement control - Operating.....	6-1
Differential lock hydraulic control - Operating	6-3

Transmission

Power shuttle transmission - Operating	6-6
--	-----

Rear remote control valves

Remote control valve Closed center mechanical remote valve - Safety rules	6-13
--	------

Rear Power Take-Off (PTO)

Two-speed rear Power Take-Off (PTO) - Grouped Safety Message	6-14
Power Take-Off (PTO) - Adjust	6-15
Power Take-Off (PTO) - Adjust	6-16
Power Take-Off (PTO) - Adjust	6-17
Two-speed rear Power Take-Off (PTO) - Operating.....	6-18
Two-speed rear Power Take-Off (PTO) - Operating.....	6-20
Two-speed rear Power Take-Off (PTO) - Operating.....	6-21

Two-speed rear Power Take-Off (PTO) - Operating	6-22
Rear Power Take-Off (PTO) automatic engagement control - Operating	6-23
Rear Power Take-Off (PTO) brake control - Operating	6-25
Power Take-Off (PTO) fender control - Operating	6-26
Rear hydraulic lift	
Safety rules	6-27
Header or attachment height system - Operating	6-28
Header or attachment height system - Operating	6-32
Rear three-point hitch	
Rear hitch - Adjust	6-36
Quick hitch - Operating	6-38
Towbar	
Rear three-point hitch - Personal safety	6-40
Rear three-point hitch - Localization overview	6-41
Towing hitch	
Brakes and controls - Safety rules	6-41
Hitches, drawbars, and implement couplings - Operating	6-42
Tires and wheels	
Wheels - General specification	6-44
Front wheels - Tire ratios	6-48
Tread and fender settings - standard MFD axles	
Brakes and controls - Adjust	6-50
Front axle system - Configure	6-51
Steering - Adjust	6-52
Fender - Adjust	6-53
Fenders and guards - Adjust	6-54
Brakes and controls - Dimension	6-55
Ballasting	
Ballasts and supports - Safety rules	6-57
Ballasts and supports - Ballast	6-57
Ballasts and supports - Ballast	6-59
Power sockets	
Electrical systems - Localization overview	6-63
Electrical systems - Localization overview	6-64

7 MAINTENANCE

General information

Grouped Safety Message	7-1
Foreword	7-3
Basic instructions	7-4
General specification - Biodiesel fuels	7-6
Engine cooling system - Basic instructions	7-8
Consumables	7-9
Capacities	7-10
General specification	7-11
Hood - Basic instructions	7-12

Maintenance planning

Maintenance chart	7-13
-------------------------	------

As required

Radiator - Check	7-15
Windshield washer fluid reservoir - Filling	7-16
Air conditioning - Check	7-17
Hand brake lever - Check	7-18
Remote control valves - Check	7-19
Radiator - Cleaning	7-20
Brake pedals - Check	7-21
Wheels - Check	7-22
Hydraulic steering line - Check	7-23

AT WARNING MESSAGE DISPLAY

Air cleaner - Cleaning	7-24
Fuel filters - Drain fluid	7-26
Brake fluid reservoir - Filling	7-27

Every 10 hours or daily

Engine - Check	7-28
----------------------	------

After the first 50 hours of operation

Maintenance - Tighten	7-29
Maintenance - Check	7-30
Maintenance - Check	7-31
Maintenance - Replace	7-32
Maintenance - Cleaning	7-33
Maintenance - Test	7-34
Maintenance - Grease	7-35

Every 50 hours

Rear three-point hitch - Grease	7-36
Tow hitch - Grease	7-37
Front axle system - Grease	7-38

Every 100 hours

Air-conditioning condenser - Cleaning	7-39
Transmission cooler - Cleaning.....	7-40
Aftercooler - Cleaning	7-41
Cab air filters - Cleaning.....	7-42
Cab air filters - Cleaning - Recirculation Filters	7-43
Accessory belt - Check - Alternator belt	7-44
Compressor drive belt - Check - Air conditioner belt	7-45
Compressor drive belt - Check	7-46

Every 300 hours

Lift oil filters - Replace	7-47
Oil filter - Replace	7-48
Transmission housing - Check	7-49
Steering knuckle and king pin - Grease	7-50
Four-Wheel Drive (4WD) axle - Check	7-51
Final drive - Check	7-52
Air cleaner - Cleaning	7-53

Every 600 hours

Engine - Replace	7-54
Fuel filters - Replace	7-56
Wheels - Tighten	7-57

Every 1200 hours or annually

Cab air filters - Replace	7-58
Cab air filters - Replace - Recirculation Filters	7-59
Air cleaner - Replace	7-60
Wheel hub - Grease	7-61
Fuel tank - Drain fluid.....	7-62

Every 1200 hours or two years

Final drive - Change fluid	7-63
Four-Wheel Drive (4WD) axle - Change fluid	7-64
Transmission housing - Change fluid.....	7-65
Accessory belt - Replace - Alternator belt	7-66
Compressor drive belt - Replace - Air conditioner belt	7-67
Compressor drive belt - Replace	7-68
Radiator - Change fluid.....	7-69

Every two years

Receiver-dryer - Replace	7-71
--------------------------------	------

Every 3600 hours or four years

Radiator - Change fluid	7-72
-------------------------------	------

Electrical System

Battery - Check	7-74
Road light - Adjust	7-76
Road light - Replace	7-77
Fuse and relay box - Replace	7-78

Fuse and relay locations

Fuse and relay box - Replace	7-79
Fuse and relay box - Replace	7-83

Storage

Frame - Storing	7-87
Frame - Storing	7-88

PTO

Clutch - Calibrate	7-89
Clutch - Calibrate	7-91

8 TROUBLESHOOTING

Fault code resolution

Instrument cluster - Part identification	8-1
Instrument cluster - General specification	8-1

Symptom(s)

Frame - Troubleshooting engine	8-2
Electrical system - Troubleshooting electrical system	8-4
Transmission - Troubleshooting	8-5
Hydraulic systems - Troubleshooting HYDRAULIC SYSTEM	8-6
Rear three-point hitch - Troubleshooting	8-7
Hydraulic service brakes - Troubleshooting	8-8
Cab climate control - Troubleshooting	8-9

9 SPECIFICATIONS

Frame - Dimension	9-1
Brakes and controls - Capacities	9-3
Rear three-point hitch - General specification	9-4
Consumables	9-5
Capacities	9-6
Transmission - Speeds	9-7
Transmission - Speeds	9-8
General specification	9-9

10 ACCESSORIES

Cab radio set - Operating.....	10-1
--------------------------------	------

11 FORMS AND DECLARATIONS

Service record 1st 50 hour, Owner copy	11-1
Service record 1st 50 hour, Dealer's copy	11-3

1 - GENERAL INFORMATION

Note to the Owner

This manual contains information concerning the adjustment and maintenance of your new machine. You have bought a reliable machine, which will ensure high performance and long-lasting service, if you maintain and use the machine correctly. Ensure that all operators read this manual carefully. Always leave this manual at the operators' disposal for immediate reference.

The NEW HOLLAND dealer will provide you with the general operating instructions for your new machine. Your dealer's service technicians were trained directly by the manufacturer. The service technicians will be able to provide any further clarification that you need regarding the operation of your machine.

The New Holland Top Service program is also available. Call 1-866-NEWHLND (1-866-639-4563) or email: na.topservice@cnh.com.

Your NEW HOLLAND dealer has the full range of genuine NEW HOLLAND spare parts. These parts are manufactured and inspected carefully to ensure high quality and accurate fitting of all necessary spare parts. When ordering parts, you should give your dealer the model code and product identification number of your new machine. Locate these numbers now and record them below. Refer to the 'General Information' section of this manual for the location of the model code and product identification numbers of your machine.

PLEASE RECORD THE FOLLOWING INFORMATION
Model :
Product Identification Number (PIN):



Warning symbol. It is used with and without signal words to alert you to potential personal injury hazards. Obey all safety messages that follow this symbol to avoid possible death or injury.

⚠ WARNING

Illustrations in this manual may show protective shielding open or removed to better illustrate a particular feature or adjustment.

Replace all shields before operating the machine.

Failure to comply could result in death or serious injury.

W0012A

The machine has been designed and built according to the highest standards of quality and it complies with all current safety regulations. However, the risk of accidents can never be completely excluded. That is why it is essential to observe elementary safety rules and precautions.

Read this manual carefully, paying particular attention to the instructions concerning safety, operation and maintenance so as to avoid the risk of injury while operating or servicing the machine.

Do not use this machine for any applications or purposes other than those described in this manual. If the machine is to be used for work involving the use of special attachments, accessories or equipment, consult your NEW HOLLAND Dealer in order to make sure that any adaptations or modifications made are in keeping with the machine's technical specifications and with prevailing safety requirements.

Any modification or adaptation which is not approved by the manufacturer may invalidate the machine's initial conformity with safety requirements.

The machine must undergo regular inspections, the frequency of which varies according to the type of use. Consult your authorized NEW HOLLAND dealer.

Always keep this manual in the operator's compartment (in the seat back, behind the operator's seat). Make sure it is always complete and in good condition. To receive extra copies of the manual or copies in languages other than that of your country of residence, please contact your NEW HOLLAND dealer.

NOTICE: *The information in this manual is provided based on the information that was available at the time the manual was written. Settings, procedures, part numbers, software and other items may change, which may affect the maintenance of the machine. Ensure that you have complete and current information from your dealer before you start any machine operation. All data given in this book is subject to production variations.*

Engine tampering statement:

ATTENTION: *The fuel system and engine on your machine are designed and built to government emissions standards. Tampering by dealers, customers, operators, and users is strictly prohibited by law. Failure to comply with this prohibition could result in government fines, rework charges, invalid warranty, legal action and possible confiscation of the machine until rework to original condition is completed. Engine service and/or repairs must be done by a certified technician only!*

Product improvements

CNH America LLC applies a policy of continuous product development and improvement. We reserve the right to make changes or improvements when possible, without incurring any obligation to make these changes or modifications to the products sold previously.

Safety rules

CALIFORNIA Proposition 65 Warning
Diesel engine exhaust and some of its constituents are known to the State of California to cause cancer, birth defects and other reproductive harm. Battery posts, terminals and related accessories contain lead and lead compounds. Wash hands after handling.

Product identification

NOTE: *Your tractor is designed according to European directives related to health and safety risks; though it has been designed to minimize all the potential risks it is mandatory to carefully read, understand and observe all the decals and labels and to always refer to information and prescriptions outlined in this manual to prevent all residual potential risks. In case you may need further assistance please do not hesitate to contact your dealer.*

Your tractor is designed and made to pull, to carry and to power a variety of mounted or towed equipment, although within some physical limits. The working speed and performance may depend on a number of various parameters, such as weather and terrain conditions. Though the tractor is designed to perform in combination with a variety of equipment, there may be a number of combinations of above parameters, for which there is severe degradation of performance of the tractor and/or its mounted or trailed equipment. If you notice degradation of performance, contact your dealer for assistance, he may have useful information for improvements, or a kit may be available to enhance the performance.

Please carefully read and consider following precautions:

- Do not use the tractor for purposes other than those intended by the manufacturer and outlined in this manual.
- Do not use the tractor beyond its limits of terrain gradient and stability. Using the tractor beyond these limits may result in a roll-over or a tip-over. Observe the recommendations given in this manual.
- Do not use the tractor on higher speeds than allowed by the load and the environment. A wet surface or other low adherence conditions may increase the braking distance or result in vehicle instability. Always adapt your traveling speed according to the load of the vehicle and the characteristics of the road
- Do not use the tractor near or on soft verges of canals and brooks or banks and verges that are undermined by rodents. The tractor may sink sideways and roll over.
- Do not use the tractor on unstable bridge heads and poor bridge floors. These constructions may collapse and cause roll - over of the tractor. Always check the conditions and load capacity of bridges, crossings and ramps before driving over them.
- Do not use equipment mounted on the tractor which is not correctly matching and firmly fixed. The use of implements or accessories that have not been approved or are not correctly connected may increase the risk of roll-over of the tractor if they come loose. Ensure that the dimensions of the three- point linkage interface of both the tractor and the equipment are matching according to the categories defined in ISO 730. Ensure that the dimensions and speed of the PTO shaft on the tractors are matching those of the equipment.
- Do not use the tractor in combination with equipment, without having consulted the specific Operator's Manual provided with the equipment. The tractor is a universal tool to carry, tow and drive a variety of equipment. This manual alone cannot provide you with all the information required for the safe operation of the combination.
- Do not use the tractor for pulling work, in cases where you do not know whether the load will yield, for instance when pulling stumps; the tractor may flip over when the stump is not yielding.
- Be cautious that the centre of gravity of the tractor may increase when loads on the front – end loader or the three point linkage are raised. In these conditions, the tractor may roll – over earlier than expected.
- Do not step down from the tractor without shutting down the PTO, shifting the transmission to park or neutral and applying the park brake, unless continued PTO operation is required for some equipment, such as pumps or wood chippers. The latter equipment may have an emergency stop device on the equipment itself, as human intervention is needed during operation. But other equipment, engaged and driven by the tractor will have no means to stop the power transmission, other than the PTO clutch of the tractor.
- You shall take the necessary precautions (e.g. assistance) to always be aware of the possible presence of bystanders, certainly when manoeuvring in confined areas, such as the farm yard and sheds. Keep people away from the tractor during work. Ask bystanders to leave the field. There is not only the risk to be overrun by the tractor, but objects ejected by some equipment mounted on the tractor, such as a rotary mower, may cause harm. Stones may be thrown further than the mowed crop. Pay the necessary attention while operating next to public roads or footpaths. Thrown objects can get projected outside the field and hit unprotected people like bikers or pedestrians. Wait to cut the edge of the field till it is clear of bystanders.
- Do not allow riders on the tractor; do not allow people to stand on the access step to the cab when the tractor is moving. Your view to the left will be obstructed and a rider risks falling from the tractor during unexpected or abrupt movements.
- Always stay clear from the implements operating area and especially do not stand between the tractor and the implement or the trailed vehicle when operating lift controls; ensure no bystanders are near these operating areas.
- Certain functions of your tractor are controlled by software and some of them are safety-related. Do not attempt to modify or download software not certified and distributed by the manufacturer. Electronic settings and logics may be destroyed and seriously affect the function of the tractor. This may result in unpredictable and unsafe behaviour of the tractor. Always refer to your dealer; he has the appropriate tools and data sets and owns the officially released software versions and updates for your tractor.

- Your tractor may be equipped with a number of sensors to control safety functions. Tripping these sensors will result in a safe operation mode. Do not attempt to bypass any function on the tractor. You will be exposed to serious hazards, and moreover, the behaviour of the tractor may become unpredictable.
- The tractor has only one operator station and this is a one man operated vehicle. There is no need for other people on or around the tractor during normal operation. Do not allow people standing on the access way to the cab when the tractor is moving. Your view to the left will be obstructed and a rider risks to fall from the tractor during unforeseen or abrupt movements.

Thank you so much for reading.
Please click the “Buy Now!”
button below to download the
complete manual.



After you pay.

You can download the most
perfect and complete manual in
the world immediately.

Our support email:

ebooklibonline@outlook.com