

**885  
Tractor  
Operators Manual**

9-11283



Reprinted






*THIS SAFETY ALERT SYMBOL INDICATES IMPORTANT SAFETY MESSAGES IN THIS MANUAL. WHEN YOU SEE THIS SYMBOL, CAREFULLY READ THE MESSAGE THAT FOLLOWS AND BE ALERT TO THE POSSIBILITY OF PERSONAL INJURY OR DEATH.*

M171B

If Safety Decals on this machine use the words **Danger, Warning or Caution**, which are defined as follows:

- **DANGER:** Indicates an immediate hazardous situation which if not avoided, will result in death or serious injury. The color associated with Danger is RED.
- **WARNING:** Indicates an potentially hazardous situation which if not avoided, will result in serious injury. The color associated with Warning is ORANGE.
- **CAUTION:** Indicates an potentially hazardous situation which if not avoided, may result in minor or moderate injury. It may also be used to alert against unsafe practices. The color associated with Caution is YELLOW.

If Safety Decals on this machine are ISO two panel Pictorial, decals are defined as follows:

- The first panel indicates the nature of the hazard.
- The second panel indicates the appropriate avoidance of the hazard.
- Background color is YELLOW.
- Prohibition symbols such as   and  if used, are RED.



# WARNING

IMPROPER OPERATION OF THIS MACHINE CAN CAUSE INJURY OR DEATH. BEFORE USING THIS MACHINE, MAKE CERTAIN THAT EVERY OPERATOR:

- Is instructed in safe and proper use of the machine.
- Reads and understands the Manual(s) pertaining to the machine.
- Reads and understands ALL Safety Decals on the machine.
- Clears the area of other persons.
- Learns and practices safe use of machine controls in a safe, clear area before operating this machine on a job site.

It is your responsibility to observe pertinent laws and regulations and follow Case Corporation instructions on machine operation and maintenance.

## TO THE OWNER OF A CASE INTERNATIONAL TRACTOR

Use this manual as your guide. If you follow the instructions given in this manual, your Case International Tractor will work well for many years.

Your Dealer can give you assistance with Case Company made parts and persons with special training that know the best methods of repair and maintenance for your tractor.

Call your Dealer if you need any assistance or information.

*Your Authorized Case Dealer*



Figure 1

**NOTE:** *Where right hand and left hand of the tractor is used in this manual it means the same as your right hand and left hand when you are in the tractor seat looking forward.*

## SERIAL NUMBERS


When ordering parts, requesting information or assistance always give the model and serial numbers of your tractor.

Write the model and serial numbers of your tractor on the lines below:

1. TRACTOR MODEL NUMBER \_\_\_\_\_
2. PRODUCT IDENTIFICATION NUMBER \_\_\_\_\_
3. ENGINE SERIAL NUMBER \_\_\_\_\_
4. TRANSMISSION SERIAL NUMBER \_\_\_\_\_
5. MFD AXLE SERIAL NUMBER \_\_\_\_\_
6. ROPS FRAME SERIAL NUMBER \_\_\_\_\_
7. CAB SERIAL NUMBER \_\_\_\_\_


### Serial Number Location

MODEL AND PRODUCT  
IDENTIFICATION NUMBER  
(P I N) PLATE




On right hand side of front bolster.

ROPS FRAME SERIAL  
NUMBER PLATE




On right hand upper frame.

ENGINE SERIAL NUMBER



On right hand side of engine.

MFD AXLE SERIAL NUMBER




On rear left hand of housing

TRANSMISSION SERIAL NUMBER



On right hand rear of transmission

CAB SERIAL NUMBER



Inside cab, right lower front

Figure 2

## TABLE OF CONTENTS

TO THE OWNER	I	OPERATING	
SERIAL NUMBERS	II,III	INSTRUCTIONS	Continued
SAFETY	VI-XI	Driving The Tractor	58,59
Safety Rules	VI	Forward/Reverse	
Before Starting	VII	Transmission	60
Operation	VIII	Two Speed Power Shift	60
Service	XI	Differential Lock	61
HAND SIGNALS	XII,XIII	Mechanical Front	
DECALS	XIV-XVI	Drive (MFD)	62
SPECIFICATIONS	1-25	Steering The Tractor	63
Diesel Engine	1,2	Stopping The Tractor	64
General	3-5	Stopping The Engine	65
Travel Speeds	6,7	Dismounting and Mounting	66
Measurements	8-10	Towing The Tractor	67
Turning Radius	11	Transporting The Tractor	67
Weights	11	Hitch System Control	68-72
Axle Capacities	11	Position Control	68
Tires and Wheels	12-15	Adjustable Stop	69
Front Wheel Tread, 2WD	16	Draft Control	70
Front Wheel Tread, MFD	17	Raise Response	71
Steering Angles, MFD	18	Drop Response	72
Oscillation Stops, MFD	19,20	Remote Hydraulic Controls	73
Rear Wheel Tread	21-23	Neutral and Float	
Diesel Fuel	24	Lockout Bar	73
Fuel Conditioner	25	Remote Hydraulic Circuits	74
OPERATING CONTROLS	26-47	Hydraulic Hose Couplers	75
Instrument Panel	26,27	Self Sealing Breakaway	
Warning Lamps	28,29	Couplers	76,77
Controls	30-39	Remote Cylinder	78
Heater Controls	40	7 Point Electrical Socket	79
Air Conditioning	40,41	Power Take Off (PTO)	80-83
Operators Seat	42,43	PTO Guards	82
Seat Belt	44	PTO Operating Safety	83
Amber Warning Lamps,		Drawbar	84
Turn Signals and		Three Point Hitch	85
SMV Symbol	45-47	Check Chains	86,87
OPERATING		Upper (Turnbuckle) Link	88
INSTRUCTIONS	48-95	Telescopic Stabilizers	88
Run-in Procedure	48	Hitching An Implement	89
Before Starting Engine	49-51	Ballasting	90,91
Starting Procedure	52,53	Front End Weights	90
Cold Starting	53-56	Rear Wheel Weights	90
Cold Temperature Operation	55	Water Ballasting	91
Using Booster Batteries	57	Measuring Wheel Slip	92,93
		Loads Matched To Tractor	94
		Adjusting Tread Positions	95
		Front Axle, 2WD	95
		Front MFD, and Rear	95

## TABLE OF CONTENTS

LUBRICATION	96-113
Hourmeter	97
Lubricant Specifications	98,100
Engine Oil Selection	98
Engine Oil Viscosity	99
Transmission and Hydraulic Sytem Fluid	100
Air Compressor	100
Grease Points	101
Lubrication Schedule	102
Lubrication Chart	103
Engine	104-106
Oil Level	104
Oil Change	105
Filter Change	106
Transmission	107-109
Oil Level	107
Oil Change	108
Filter Change	109
MFD Axle	110,111
Differential Oil Level	110
Differential Oil Change	110
Hub Oil Level	111
Hub Oil Change	111
Front Wheel Bearings	112,113
PREVENTIVE MAINTENANCE	114-159
Removing Hood, Grille and Side Covers	114,115
First Service	116-118
Drive Belt Adjustment	116
Engine Air Intake	117
Battery Electrolyte	117
Battery Maintenance	118
Servicing Schedule	119
Every 10 Hours	120-122
Every 40 Hours	123
Every 200 Hours	124,125
Every 400 Hours	126
Every 800 Hours	127-133
Every 2 Years	134-136

PREVENTIVE MAINTENANCE	Continued
Removing Air From The Fuel System	137
Brakes	138-141
Pedal Height	138,139
Removing Air	140
Park Brake Adjustment	141
Engine Clutch	142,143
Pedal Height, ROPS	142
Pedal Height, CAB	143
Removing Air	143
Front Wheel Alignment	144-146
2WD Adjustable Axle	144
2WD Rigid Cast Axle	145
MFD Axle	146
Cab Air Cleaners	147
Air Conditioning	148
Electrical System	149-156
Head Lamps	149,150
Work/Tail Lamps	151-153
Turn/Warning Lamps	154,155
Fuses	156
Panel Lamps	156
Roll Over Protection Structure (ROPS)	157-159
Tractor Roll Over	157
Safety	158
Seat Belt	158
Maintenance	159
NOTES	160

## SAFETY

### Safety Rules

Understand that your safety and the safety of other persons is measured by how you service, and operate this machine. Know the positions and operations of all controls before you try to operate. **MAKE SURE YOU CHECK ALL CONTROLS IN A SAFE AREA BEFORE STARTING YOUR WORK.**

**READ THIS MANUAL COMPLETELY** and make sure you understand the controls. All equipment has a limit. Make sure you understand the speed, brakes, steering, stability, and load characteristics of this machine before you start to operate.

The safety information given in this manual does not replace safety codes, insurance needs, federal, state and local laws. Make sure your machine has the correct equipment needed by the local laws and regulations.

J I Case is continuing to work for your safety: by making tractors with better protection and by giving these rules for safe operation.



**THIS SAFETY ALERT SYMBOL INDICATES IMPORTANT SAFETY MESSAGES IN THIS MANUAL. WHEN YOU SEE THIS SYMBOL, CAREFULLY READ THE MESSAGE THAT FOLLOWS AND BE ALERT TO THE POSSIBILITY OF PERSONAL INJURY OR DEATH.**



## Before Starting



**CAUTION:** Provide a first aid kit for use in case of accident.



**CAUTION:** It is good practice to carry a fire extinguisher on the tractor. Be sure that the extinguisher is properly maintained and be familiar with its proper use



**CAUTION:** Check the machine for leaks or any parts that are broken, not working correctly, or not there at all. Before you start the machine, tighten all caps, dipsticks, battery covers, etc.



**WARNING:** Before starting the engine, be sure all operating controls are in neutral. This will ease starting loads on the starter and batteries and will eliminate the accidental start up of PTO driven equipment.



**WARNING:** Before starting engine study Operators Manual safety messages.

Read all safety signs on machine.

Clear the area of other persons.

Learn and practice safe use of controls before operating.

It is your responsibility to understand and follow manufacturers instructions on machine operation, service, and to observe pertinent laws and regulations.

Operator and Service Manuals may be obtained from your equipment dealer.



**WARNING:** To help prevent injury:

**BEFORE STARTING ENGINE** - Put shields in place. Sit in the seat. Place controls in neutral.

**BEFORE OPERATING MACHINE** - Clear people away. No riders. Fasten seat belt.

**WHEN OPERATING MACHINE** - Keep away from power driven parts. Avoid steep slopes, embankments, ditches and rough terrain. Reduce speed when turning. In high speed travel, couple brake pedals together where applicable. On road travel, use flashing warning lights where permitted and keep SMV emblem visible from rear.

**WHEN MACHINE IS STOPPED** - Engage park lock or brake. Lower raised equipment to ground. Stop engine before dismantling to service or clear machine(s).

## Operation

**WARNING:** Engine can start with transmission in gear when neutral or safety start switch is by-passed.

1. Do not connect across terminals on starter.

2. Attach booster batteries according to safe method in Operators Manual. Then use recommended starting procedure from operators seat.



3. When necessary, repair electrical system components promptly so that "jump starting" will not be attempted.

Machine run-away can cause injury or death to operator and by-standers.



**WARNING:** Collision of high speed road traffic and tractors or implements can cause personal injury or death. On roads, use flasher/lights according to local laws. Keep SMV emblem visible.



**WARNING:** Tractor travel speed should be such that complete control and tractor stability is maintained at all times. Where possible, avoid operating the tractor near ditches, embankments and holes. Reduce speed when turning, crossing slopes, and on rough, slick, or muddy surfaces.



**CAUTION:** Stop, look and listen before entering a highway, stay on your side of the road and pull over to let faster traffic pass. Slow down and signal as you turn off.



**WARNING:** A frequent cause of personal injury or death is persons falling off and being run over. Do not permit others to ride. Only one person - the operator - should be on a tractor when it is in operation.



**CAUTION:** Try to balance the load primarily on the implement wheels - as in loading a trailer or spreader. Avoid overloading the drawbar. Add front end weights for improved stability. Engage the clutch smoothly, avoid jerking and use the brakes cautiously to avoid jack-knifing.



**WARNING:** *Be certain all hitch retaining pins are securely engaged in the implement lift pins and both telescopic lower link latches are fully engaged before transporting or pulling the implement.*



**WARNING:** *Rear upset can result if pulling from wrong location on tractor. Hitch only to the drawbar. Use 3 point hitch only with the implements designed for its use - not as a drawbar.*



**CAUTION:** *Operate the tractor with the cab door closed to provide proper ROPS protection and to properly utilize the heating, ventilating or cooling systems.*



**WARNING:** *Stay off slopes too steep for safe operation. Shift down before you start up or down a hill with a heavy load. Avoid "free wheeling".*



**WARNING:** *Rotating machine parts, stay clear, keep shields installed to help protect from clothing entanglement and injury. Wear close-fitted clothing.*



**WARNING:** *To prevent personal injury due to PTO driven machine shaft bottoming or separating, drawbar must be properly positioned in pivot bracket.*

**PTO Shaft**

**PTO Shaft End To Hitch Pin Hole**

540 RPM 6 Spline  
1000 RPM 21 Spline

14.00 inch (356 mm)  
16.00 inch (407 mm)



**CAUTION:** *To provide more secure hand and foot mobility, preventing slipping and possible injury, always face the tractor when mounting and dismounting.*



**CAUTION:** *Make sure that the rim bolts, hub bolts or nuts, or hub clamp bolts are tightened to specifications. Check these torques after the first 10 hours and thereafter every 50 hours of operation until torques remain constant.*



**WARNING:** *Lower or block hydraulically or mechanically elevated implements and other attachments before servicing or when leaving the equipment.*



**CAUTION:** *When remote cylinders are connected to the hydraulic system, cycle the control lever about three times to remove air from the cylinder and hoses. With air in the system raised equipment can drop accidentally and cause personal injury or machine damage.*



**CAUTION:** *The implement should be lowered to the ground before uncoupling of the remote hydraulic hoses.*



**WARNING:** *Contact with overhead power lines can cause severe electrical burns or death from electrocution. Make sure there is enough clearance between raised equipment and overhead power lines.*

## Service



**CAUTION:** *Never use gasoline, naphtha or any other volatile material for any cleaning purposes. These materials may be toxic and/or flammable.*



**WARNING:** *Never operate the engine in a closed building. Proper ventilation is required under all circumstances.*



**WARNING:** *Battery explosion and/or damage to electrical components can result from improper connection of booster batteries or charger. Connect positive to positive and negative to negative. Externally, battery acid can cause burns and blindness, and taken internally is poison.*



**WARNING:** *Extreme care must be exercised when adjusting and checking hitch and control linkage when the engine is running and when linkage is under hydraulic or mechanical load. Study the linkage and hitch travel. Keep the hands, arms, legs and feet out of the travel arc of the hitch and linkage.*



**WARNING:** *Do not remove, install or make repairs to a tractor tire on a rim. Take the tire and rim to a tire shop where persons with special training and special safety tools are available. If the tire is not in correct position on the rim, or if too full of air, the tire bead can loosen on one side and cause air to leak at high speed and with large force. Because the air leak can thrust the tire in any direction, and with much force, you will be in danger of injury.*



**WARNING:** *Rotating fan and belts . Contact can injure . Keep clear.*



**WARNING:** *Coolant can spray under pressure. Close valves before removing coolant conditioner filter.*

**Buy Now**



Our support email:

[ebooklibonline@outlook.com](mailto:ebooklibonline@outlook.com)