Instructions For Setting Up

AND OPERATING

Case

MODELS T320, T321, T322, T340, T341 and T342 CULTIVATORS ON CASE 312 TRACTORS WITH DUAL OR SINGLE FRONT WHEEL AND 351 TRACTORS



J. I. CASE COMPANY

Racine, Wisconsin, U. S. A.

Rock. Form 9-82141 First Edition 200 9-57

INTRODUCTION

The CASE Models T320, T321, T322, T340, T341 and T342 Series, Two and Four Row Cultivators have been adapted for use on Model 312 and 351 Tractors equipped with either single or dual front wheels.

The guide pins for attaching the front cross pipes will be used in the mounting rail extensions, instead of in the tractor mounting rails as mounted on Model 301 and 311 Tractors.

Special mounting pivots and brackets are furnished to attach these two and four row cultivators on Model 312 and 351 tractors. A special spacer plate is furnished for mounting the cultivators on 351 tractors only and is not used when the cultivators are to be mounted on 312 tractors.

THE FOLLOWING INSTRUCTIONS ARE SUPPLEMENTARY TO AND MUST BE USED IN CONJUNCTION WITH THE OPERATOR'S INSTRUCTION MANUAL, FORM D1943, FOR TWO ROW CULTIVATORS AND D1944 FOR FOUR ROW CULTIVATORS. MANUAL D2009 WILL ALSO BE USED WHEN FLEXIBLE REAR GANGS ARE USED.

MOST FARM ACCIDENTS, like industrial, home, and highway accidents, are caused by the failure of some individual to observe simple and fundamental safe rules or precaution. For this reason farm accidents, just as other types of accidents, can be prevented by recognizing the cause of accidents and doing something about it before the accident occurs.

-National Safety Council.



Our support email: ebooklibonline@outlook.com