

8010 Diesel Tractor



OPERATORS MANUAL

8010 Diesel Tractor

OMR30814 H0 English



OMR30814 H0

LITHO IN U.S.A. ENGLISH

To the purchaser

Your new John Deere 8010 Tractor is a powerful, versatile, heavyweight performer. Built to the traditionally high standards of John Deere, this tractor will handle large-capacity tools in the toughest field conditions at high speed and with unequalled economy. Added to the tractor's tremendous capacity for work are such modern features as four-wheel drive, power steering, air brakes, heavy-duty hydraulic clutch, "on the go" gear shifting, and oscillating front and rear sections which enable the tractor to cross over rough ground and cling to hillsides with great stability. New operating ease and comfort, hydraulic power when and where you need it, the ability to match engine power and transmission speed to any job, outstanding dependability, and simplicity of lubrication and service are all in this great new tractor.

When used with equally advanced John Deere tools and implements, your 8010 will deliver all the power you need for better, easier, and more profitable farming.

At the time the tractor was delivered, the John Deere dealer discussed with you its safe operation and proper care. However, before putting the tractor to work, read this manual. It contains complete instructions for operating the tractor, caring for it, and taking full advantage of its many time and labor-saving features. After reading the manual, keep it in a convenient place for quick and easy reference if questions arise concerning operation, lubrication, or service.

The service policy which you received with you new tractor certifies that the tractor was properly inspected and prepared for delivery by your John Deere dealer. Keep this policy in a safe place and present it to the dealer whenever services which it authorizes are required.

Your John Deere dealer wants to help you get the most value from your new tractor. His skilled servicemen can handle every job efficiently. These men are trained in modern service methods and have all necessary tools and equipment.

When in need of parts, be prepared to furnish your dealer with the serial number of the tractor and the serial number of the engine or other component for which parts are required. This information will help the dealer give you quick, efficient service.

The tractor serial number plate is located on the left-hand side of the front section (bogie). The serial number of the engine is located on the right-hand side of the valve rocker arm cover. Serial numbers of other components are prominently displayed.





contents

2	specifications
4	controls and instruments
8	operation
26	safety rules
28	fuels and lubricants
32	lubrication and periodic service
50	service
63	tractor storage
65	trouble shooting
72	index



specifications

POWER

Engine horsepower Drawbar pull	More than 200 h.p. 9,000 to 11,000 lbs.
SPEEDS	
1st	2 mph
2nd	2-7/8 mph
3rd	3-7/8 mph
4th	5 mph
5th	6-1/3 mph
6th	8-1/8 mph
7th	11 mph
8th	14 mph
9th	18 mph
	-7/8 mph
High reverse 5	-5/8 mph


ENGINE GM 2-cyc	le, 6-cylinder
Bore	4.25 in.
Stroke	5.00 in.
Displacement	425 cu. in.
Compression ratio	17 to 1
Rated speed	2100 rpm

CAPACITIES (U.S. MEASURE- MENTS) Fuel tank Hydraulic system Cooling system Crankcase Transmission Drop housing case Axle housing and planetary Oil bath air cleaner Clutch and auxiliary reservoir Hydraulic pump housing	106 gals. 25 gals. 12 gals. 4.5 gals. 2.2 gals. 1.6 gals. 7 gals. 1.6 gals. 9 gals. 3.3 qts.
FUEL SYSTEM Recircu full-f	llating bleed type with low strainer and filter
ELECTRICAL SYSTEM Starting Lights and accessories	

LUBRICATION SYSTEM


Туре	_		_		_	_	_	_	 _	•	•	•	•
Filter	s	•			•	•		•	•			•	•

Full pressure, force feed One full-flow, one bypass



John Deere 8010 Diesel Tractor, right-hand side view

COOLING SYSTEM	Bypass, pressure type	HYDRAULIC SYSTEM Choice of two or three val double-acting remote cy					
TRANSMISSION			operation	n. 3-point hitch avail-			
Туре	Syncro-mesh, 2-range, air as- sisted between ranges		able	-			
Speeds	9 forward, 2 reverse	TIRE SIZES	23.1 18-26	, 12-ply, or			
			18.00 x 25, 20-ply				
CLUTCH	Heavy-duty, hydraulically actu-	DIMENSIONS	SIONS				
	ated	Height to top of steering	g wheel 8 f	t. 3 in.			
		Height to top of exhaust	pipe 9	ft. $4-1/2$ in.			
STEERING	Fully hydraulic power steering	Width over tires	96	in.			
		Wheelbase		0 in.			
BRAKES		Length (grille to drawb					
Туре	4 drums with internal expanding shoes	Turning radius					
Operated by	Compressed air	WEIGHT					
Parking brake	Mechanical	Front only (without liqu	id ballast) 1	3,750 lbs. (67%)			
		Rear only (without liqui					
DRIVE AXLES	Heavy-duty with planetary reduc-	Total without liquid ba	,	/			
	tion	Total with liquid ballast 26,700 lbs.					



John Deere 8010 Diesel Tractor, left-hand side view

Thank you so much for reading. Please click the "Buy Now!" button below to download the complete manual.



After you pay.

You can download the most perfect and complete manual in the world immediately.

Our support email:

ebooklibonline@outlook.com